

INNOVATION



FRSE-F2

UNIVERSAL FOAM FIRE EXTINGUISHER - 2 LITERS

- Suitable for extinguishing Lithium-ion batteries

- Operational down to -15°C

Firefighting Ability



Class A (8A): Firefighting Ability

Class B (55B): Fires of flammable liquids or substances that become liquid.

Successfully tested for extinguishing

A: Lithium cell and battery fires.

75F: Lithium cell and battery fires.

D: Fires of light and alkali metals (e.g. magnesium, titanium or lithium).

Extinguishing agent:

FRS EXcellent 1 (100% premix)

A ready-to-use fire extinguishing mixture designed for direct filling into fire extinguishers or spray systems.

It is effective against:

Class A (8A): Including lithium-ion battery fires. In tests, 400 ml of the mixture successfully extinguished cylindrical Li-ion batteries with a total capacity of 300 Wh—with no re-ignition.

Class B (55B): Minimum required extinguishing agent volume 2 litres.

Class D: Suitable for flammable metals.

Class F (75F): Minimum required extinguishing agent volume 1.2 litres.



CE

Filling quantity	2 liters
Release agent	Nitrogen (N2)
Discharge Time	Minimum 12 seconds
Test pressure	27 bar
Operating pressure	15 bar
Operating Temperature Range	-15°C to +60°C
Total weight	3.45 kg
Height	360 mm
Bottle diameter	110 mm

The fire extinguisher is manufactured in accordance with current European EN3 standards and under a certified ISO 9001 production and service system.

Call us and make an appointment with us. You can always find a cup of good coffee and a quality conversation with us. For more information visit our website.

T +420 605 200 555 E office@firesi.cz

WWW.FIRESI.CZ